


Product key

Magnetic Sheet separator



Product	
HSS	Magnetic Sheet separator
HSSZ	Special magnetic Sheet separator

Magnet quality	
F	GSFD-33, Br 4100 gauss, Tmax 225°C
N	N35, Br 11 200 gauss, Tmax 80°C /
	N38, Br 12 600 gauss, Tmax 80°C /
	N45, Br 13 700 gauss, Tmax 80°C
HT	N35SH, Br 12 200 gauss, Tmax 150°C
ET	N35EH, Br 12 200 gauss, Tmax 200°C
ST	Sam-cobalt GSS-28, Br 11 000 gauss, Tmax 350°C
ES	N52, Br 14 800 gauss, Tmax 80°C

Type	
BA	Basic
PF	Pneumatic operated – Flat front
PA	Pneumatic operated – Arched front
RD	Rod
ZZ	Special type

Width x height (thickness) [mm] (for type BA/PF/PA)
D (Diameter) [mm] (for type RD)

For type BA:		
Type:	Ferrite	Neodymium
0	73x29	43x22
1	n/a	73x22
2	114x47	114x22
3	154x47	n/a
4	204x92	n/a
5	304x97	n/a

Length [mm]

Options	
B	Basic
C	Connection for air nozzles
N	Including air Nozzles
S	Incl. Sensors for on/off detection
Z	Special type